



Arké P710



Mesos P711



Eos P712




Olos P713



Trias P714

**Sizes**



24" x 24" Field Tile  
Polished, Unpolished & Structured  
(Nominal 23 1/2" x 23 1/2")  
(Nominal 60.0 cm x 60.0 cm)  
Square feet per carton: 15.49  
Pieces per carton: 4



12" x 24" Field Tile  
Polished, Unpolished & Structured  
(Nominal 11 3/4" x 23 1/2")  
(Nominal 30.0 cm x 60.0 cm)  
Square feet per carton: 15.49  
Pieces per carton: 8



18" x 18" Field Tile  
Polished, Unpolished & Structured  
(Nominal 17 3/4" x 17 3/4")  
(Nominal 45.0 cm x 45.0 cm)  
Square feet per carton: 13.13  
Pieces per carton: 6

Grout joint recommendation: 1/16",  
1/8" when used in a pattern

Tile thickness: 3/8"

Shade Variation:  (High)

**Application**

	Residential	Light Commercial	Commercial
Floors	X	X	X
Walls and Backsplashes	X	X	X
Counters	X	X	X
Pool Linings	X	X	X

*Suitable for exterior patios (unpolished\* and structured field tile), including pool decks (structured field tile only) and walls in freezing and non-freezing climates when proper installation methods are followed. Special care should be taken when grouting with dark pigmented colors. A grout release is recommended to prevent finely powdered pigments from lodging in the pores of the tile surface. Not for use on ramps. Manufactured in accordance with ANSI A137.1 standards. For additional application information refer to "Factors to Consider" at [www.daltile.com/CommercialFactors](http://www.daltile.com/CommercialFactors).*

\* residential exterior patios only.

**Trim**

Type	Number	Size
Bullnose	S-43H9	3" x 18"
	Polished & Unpolished	



**Maintenance:** Routine maintenance will keep your tile looking new for years to come. Under normal situations, the tile can be cleaned using clear water with a neutral tile cleaner. Always follow-up with a rinse of clear water. No waxes or sealers are recommended for this product.

**Test Results**

	ASTM#	Result
Water Absorption	C373	<0.5%
Breaking Strength	C648	>450 lbs.
Scratch Hardness	MOH's	8.0
Chemical Resistance	C650	Resistant
Coefficient of Friction	Unpolished	Wet ≥0.60
		Dry ≥0.70
	Polished	Wet ≥0.50
		Dry ≥0.70
Structured	Wet ≥0.65	
	Dry ≥0.80	



Each tile is rectified and modular which allows for the use of smaller grout joints.