

POLYBLEND® GROUT RENEW

- **One step stain and sealer**
- **Makes grout joints look like new**
- **Renew or change grout color**
- **Stain and fade resistant**

PRICE



PRODUCT DESCRIPTION

Polyblend® Grout Renew is a water-based, acrylic, urethane stain and sealer for renewing or changing the color of cement grout joints. Formulated with fade-resistant pigments, Grout Renew seals the grout against stains while it colors. Available in all 48 Polyblend colors to complement any tile or stone installation.

USES

- Use to restore or change grout color of cement grout joints.
- Interior or exterior use.

LIMITATIONS

- Not recommended for use underwater.
- Do not use solvent-based cleaners on recolored grout joints. We recommend TileLab® Grout & Tile Cleaner or a StoneSpecific™ cleaner & resealer.
- Unglazed tile will require sealing prior to coloring to ensure Grout Renew isn't absorbed into the tile. We recommend TileLab SurfaceGard® Penetrating Sealer.
- Do not apply when ambient temperature is below 50° F (10° C) or above 80° F (27° C).

SURFACE PREPARATION

Existing grout joints should be clean and free of all sealers and contaminants which might inhibit bonding and absorption of colorant. Prepare existing joints by cleaning with TileLab Sulfamic Acid Cleaner or Grout Haze Remover according to directions on the container. Grout must be cured and dry prior to application. Test a small inconspicuous area prior to application. Allow to dry 24 hours to see if desired results are obtained.

APPLICATION

Shake well before using. If more than one bottle of the same color is being used mix all bottles together in a separate container. Apply to dry grout joints. Apply small bead of Grout Renew directly to center of joint. Work back and forth with a soft-bristled toothbrush to assure a thin, even

application. Do not allow it to bead or puddle. Do not allow Grout Renew to dry on tile surface, wipe it off as you go. Work small areas at a time.

DRYING TIME

Ready for light traffic in 2 to 4 hours, normal traffic in 24 hours. Do not expose to water for 72 hours. Avoid scrubbing joints.

COVERAGE

Approximately 80 sq. ft. per 1/2 pint (7.4 M² per 237 ml) for a 4" x 4" (10 x 10 cm) tile with a 1/4" (6 mm) joint.

CLEANUP

Clean tools and hands with water before material dries.

SAFETY

Do not take internally. Harmful if swallowed. If ingested, induce liquids. Do not induce vomiting. Avoid eye contact and prolonged contact with skin. In case of eye contact, flush eyes with water for 15 minutes and call a physician immediately. Keep out of reach of children.

ORDERING INFORMATION

ITEM CODE	SIZE	COLOR	PACKAGE
USA			
GCLXXXHPT	1/2 Pint (237 ml)	All 48 Polyblend colors available.	Bottle
Canada			
CGCLXXXHPT	1/2 Pint (237 ml)	All 48 Polyblend colors available.	Bottle

LIMITED WARRANTY

Custom Building Products ("Custom") warrants to the original consumer purchaser that its product shall be free from defects in material and workmanship under normal and proper usage for a period of one year following the date of original purchase. Custom's sole liability under this warranty shall be limited to the replacement of the product. Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty will not extend to any product which has been modified in any way or which has not been used in accordance with Custom's printed instructions. Custom makes no other warranties either express or implied. This warranty gives you specific legal rights, and you may have other rights that vary from state to state.



CUSTOM®
BUILDING PRODUCTS